

monty[®]
TYRE CHANGERS

8800

NEW

*YOUR TYRE
CHANGER
OF CHOICE*

SMARTSPEED



HOFMANN[®] 

HIGH PRODUCTIVITY EASE OF USE LESS TECHNICIAN'S FATIGUE

monty® 8800 combines the high productivity features of a tabletop tyre changer and the high performances of those leverless.



POWERMONT™

The innovative system to mount & demount tyres

SMART SPEED™



smartSpeed™ continuously controls the mount/demount conditions in order to provide the optimum torque/speed combination to the motor

- **SAFE:** always the most appropriate torque to avoid interruption of the process and damages to tyre and rim
- **FAST:** automatically selects the maximum speed possible up to 20 rpm
- **EASY TO USE:** smartSpeed™ automatically sets the speed to the torque required





OPTIMUM BEAD BREAKER SYSTEM

The most performing solution for any tyre's types



Dynamic bead breaker

- The bead breaking of choice for RFT, UHP and low aspect ratio tires – Precise and damage free
- Disk position synchronized by servo drive – Fast & precise
- Disk pneumatic tilt - Optimum performance with stuck beads
- Ergonomic & effortless



On floor bead breaker *

- The fastest solution for tyres with soft sidewall and high aspect ratio
- Ease of use
- Shovel actuated by a switch on the handle
- On floor bead breaker assures high productivity with standard tyres

(*) monty® 8800s and higher models

QUICKLOK™

The fast and effortless automatic wheel clamping

- Electromechanical lock and unlock of the wheel via switch on the control panel for easy clamping
- Center post design - more flexibility in wheel clamping
 - No restriction on rim size
 - No wheel damage
 - No need to “push” the rim into the jaws
 - No jaw protection
- Constant locking force
- Fast as a tabletop tyre changer with steel wheels
- Easy and damage free with UHP and run-flat tyres
- Effortless

POWERMONT™

The innovative system
to mount & demount tyres

monty®
TYRE CHANGERS

FAST

- Automatic synchronization of all tools positions
- Fast disengage and repositioning of the mount/demount tool
- Standalone tool for lower bead mounting

EASY TO USE

- Control of the mount/demount tool's trajectory
- Intuitive and simple control of the operations


SAFE

- Thin mount / demount finger protects the bead from stress during mounting
- Servo assisted movement of the mount / demount tool, the finger follows the rim profile and prevents damages of TPMS and valve
- Integral and soft tool protection avoids rim damage


RELIABLE

- Long lasting mount / demount tool made of steel with integrated plastic protection

Demounting sequence



Mounting sequence



Features	monty® 8800b	monty® 8800s
Clamping range	12" - 30"	12" - 30"
Max tyre width	380 mm	380 mm
Max wheel dimension	47"	47"
smartSpeed™	CW 7 - 20 rpm	CW 7 - 20 rpm
quickLOK™	standard	standard
powerMONT™	standard	standard
Optimum bead breaker system	n.a	standard
Bottom bead viewer	mirror	mirror
Wheel lift & Tools storage	option	option

EMEA-JA
Snap-on Equipment s.r.l. - Via Prov. Carpi, 33 - 42015 Correggio (RE)
Phone: +39 0522 733-411 - Fax: +39 0522 733-479 - www.hofmann-equipment.com

Austria
Snap-on Equipment Austria GmbH - Hauptstrasse 24/Top 14 - A-2880 St. Corona/Wechsel (RE)
Phone: +43 1 865 97 84 - Fax: +43 1 865 97 84 29 - www.hofmann-equipment.com

France
Snap-on Equipment France - ZA du Vert Galant - 15, rue de la Guivernone BP 97175
Saint-Ouen-l'Aumône - 95056 Cergy-Pontoise CEDEX
Phone: +33 134 48 58-78 - Fax: +33 134 48 58-70 - www.hofmann-equipment.com

Germany
Snap-on Equipment GmbH - Konrad-Zuse-Straße 1 - 84579 Unterneukirchen
Phone: +49 8634 622-0 - Fax: +49 8634 5501 - www.hofmann-equipment.com

Italy
Snap-on Equipment s.r.l. - Via Prov. Carpi, 33 - 42015 Correggio (RE)
Phone: +39 0522 733-411 - Fax: +39 0522 733-410 - www.hofmann-equipment.com

United Kingdom
Snap-on Equipment Ltd. - Unit 17 Denney Road, King's Lynn - Norfolk PE30 4HG
Phone: +44 118 929-6811 - Fax: +44 118 966-4369 - www.hofmann-equipment.com