

8600





8600

FOR PASSENGER CAR TYRES



The integrated demounting finger supersedes the conventional tyre lever. It pulls the bead over the rim edge, being as gentle to the tyre as can be and reducing the effort of the operator.



ESDBTM

The unique electronically synchronised dual-disc bead breaker with servo drive. Bead breaking in an upright position: faster, easier, ergonomic and effortless. The bead roller is applied to detach both soft and stiff beads.



Match-mounting

The geodyna® 9000p diagnostic wheel balancer identifies run-out vibrations that can be eliminated only by repositioning the tyre on the rim.

The monty® 8600 makes match-mounting easy.



Demounting of the lower bead by means of the bead breaker disc. Fast and easy.

Tyre inflator

Ergonomically operated by the pedal. Also available with top-side bead seating kit (GP version).

Integrated demounting finger

Improves productivity as it works fast with standard and hard sidewall tyres.

Tool box

Ergonomic storage for valves and tools.

Centre-type quick fit wheel clamping flange

Fast, safe and precise.

Wheel lift

Fast and ergonomic, it reduces the effort when mounting and demounting large and heavy wheels.

2-speed inverter

Precision and high torque at low speed for the best mounting and demounting result.









| TECHNICAL DATA | | | |
|----------------------------|---|--|--|
| Maximum wheel diameter | 1200 mm / 47" | | |
| Maximum wheel width | 15" – Standard and reverse mounted rims | | |
| Maximum wheel weight | 70 kg | | |
| Clamping flange speed | 7 / 14 rpm | | |
| Maximum bead breaker force | 11500 Nm | | |
| Dimensions (W x D x H) | 1700 x 1500 x 2260 mm | | |
| Machine weight | 430 kg | | |
| Compressed air supply | 8 – 12 bar | | |
| Power supply | 230 VAC 1ph 50/60Hz | | |
| | | | |

| CONFIGURATIONS | | | | |
|---|----------|----------|-------------|------------|
| | Platinum | Gold | Advanced GP | Advanced |
| ESDB™ (electronically synchronised dual-disc bead breaker) | • | • | • | • |
| Top-side bead seating device GP | • | | • | |
| Bead press arm MH | • | • | optional * | optional * |
| Sidewall press arm | • | • | optional | optional |
| Laser pointer | • | • | | |
| Wheel lift | • | optional | optional | optional |
| Certified by wdk | • | • | | |

^{*} required for wdk certificate

OPTIONAL EXTRAS

Reverse mounting kit 4031245

Closed-centre rim kit 4030515

Adhesive weight removing tool 4025573

Infrared thermometer for measurement of tyre temperature 4-00680A









Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.hofmann-europe.com

Austria
Snap-on Equipment Austria GmbH - Hauptstrasse 24/Top 14 - A-2880 St. Corona/Wechsel (RE)
Phone: +43 1 865 97 84 - Fax: +43 1 865 97 84 29 - www.hofmann-europe.com

 $\begin{tabular}{ll} France \\ Snap-on Equipment France \cdot ZA du Vert Galant \cdot 15, rue de la Guivernone BP 97175 \\ \end{tabular}$ Saint-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX Phone: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.hofmann-france.fr

GermanySnap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen
Phone: +49 8634 622-0 · Fax: +49 8634 5501 · www.hofmann-deutschland.com

Italy
Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-410 · www.hofmann-italia.com

United Kingdom Snap-on Equipment Ltd. - Unit 17 Denney Road, King's Lynn - Norfolk PE30 4HG Phone: +44 118 929-6811 - Fax: +44 118 966-4369 - www.snapon-equipment.co.uk



