

HIGH-VOLUME WHEEL BALANCERS

geodyna®  
WHEEL BALANCERS

7340



**HOFMANN**® 

# ***GEO TOUCH™ TECHNOLOGY: THE NEXT MILESTONE FOR DIGITAL BALANCERS***

- Wide touchscreen display
- Clear and intuitive
- Large digits, bright indicators



## *GEO TOUCH™*

---

Makes a digital balancer as intuitive and easy to operate as a video balancer.

Intuitive operation given by the wide screen, large digits for the amount of the balance weight and bright indicators for the weight position.

Ergonomics and ease of use with touchscreen user interface.





## Smart Sonar™

---

Automatic, non-contact rim width acquisition delivers greater accuracy and ease of use for a 30% savings in complete process when compared to manual operation.



## easyALU™

---

Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.



## Stop in position

---

Touch the screen to automatically rotate the wheel to weight application position.



## easyWEIGHT™

---

Pinpoint laser identifies exact weight placement location for increased accuracy and efficiency.





### Multiple users

---

Two operators can operate with the balancer simultaneously and quickly recall their rim dimensions.



### Power Clamp™

---

Patented automatic Power Clamp™ electromechanical clamps the wheel accurately with a constant force, reducing the opportunity for chasing weight.



### VPM technique

---

Measurement system for high precision and repeatability.



### QuickBAL™

---

30% reduced cycle time, less than 4,5 seconds, maintaining the same high accuracy.

# 7340

## ***DESIGNED FOR PROFESSIONALS WHO WANT PREMIUM PERFORMANCE***

The ideal solution: High performance, small footprint and accurate balancing results.

### ***S***

#### ***SONAR***

Automatic, non-contact rim width acquisition delivers greater accuracy and ease of use for a 30% savings in complete process when compared to manual operation.

### ***L***

#### ***LASER***

easyWeight pinpoint laser identifies exact weight placement location for increased accuracy and efficiency.

### ***P***

#### ***POWER CLAMP***

Patented automatic Power Clamp electromechanically clamps the wheel accurately with a constant force, reducing the opportunity for chasing weight.







# 7340



# geodyna®

WHEEL BALANCERS

FEATURES	7340S	7340L	7340P
Sonar	•	•	•
Laser		•	•
Power Clamp			•

## TECHNICAL SPECIFICATIONS

Vehicles supported	Passenger cars / light trucks / VAN / SUVs / motorcycles
Diameter of shaft	40 mm
Length of shaft	225 mm
Measuring speed	200 rpm
Angular resolution	± 0.35°
Balancing accuracy	1 g
Start/Stop cycle	4.5 seconds

## Data Entry

Rim diameter range	Manual 8"–32" Semi Automatic 8"–26"
Offset range	1"–20"
Rim width range	1"–20"








## Wheel Specs

Max. wheel diameter	42" (1050 mm)
Wheel width range	3"–20" (508 mm)
Max. wheel offset (without optional spacers)	up to 260 mm
Max. wheel weight	70 kg (154 lbs)





## Dimensions and Weight

Machine Dimensions L x W x H (Machine only, wheel guard open)	138 x 88 x 167 cm
Machine Net Weight	90 kg

## INCLUDED ACCESSORIES

	Weight Plier
	Adhesive Weight Removal Tool
<td>Calibration Weight and Spacer 2"</td>	Calibration Weight and Spacer 2"
	Storage Peg (4x)
	Pressure Ring
	Pressure Cup
	Large Cone (Ø 96 – 116 mm)
	Medium Cone (Ø 72 – 99 mm)
	Small Cone (Ø 42 – 82 mm)

## Optional accessories

	BW2010 – Pneumatic wheel lift for car wheel balancers
	Large clamping hood (Ø 200 mm) for alloy rims
	Set of 9 low-taper centering collets 52.5 – 122 mm
	Stud-hole flanges (see price list for different types)

EMEA-JA  
Snap-on Equipment s.r.l. - Via Prov. Carpi, 33 - 42015 Correggio (RE)  
Phone: +39 0522 733-411 - Fax: +39 0522 733-479 - www.hofmann-equipment.com

Austria  
Snap-on Equipment Austria GmbH - Hauptstrasse 24/Top 14 - A-2880 St. Corona/Wechsel (RE)  
Phone: +43 1 865 97 84 - Fax: +43 1 865 97 84 29 - www.hofmann-equipment.com

France  
Snap-on Equipment France - ZA du Vert Galant - 15, rue de la Guivernone BP 97175  
Saint-Ouen-l'Aumône - 95056 Cergy-Pontoise CEDEX  
Phone: +33 134 48 58-78 - Fax: +33 134 48 58-70 - www.hofmann-equipment.com

Germany  
Snap-on Equipment GmbH - Konrad-Zuse-Straße 1 - 84579 Unterneukirchen  
Phone: +49 8634 622-0 - Fax: +49 8634 5501 - www.hofmann-equipment.com

Italy  
Snap-on Equipment s.r.l. - Via Prov. Carpi, 33 - 42015 Correggio (RE)  
Phone: +39 0522 733-411 - Fax: +39 0522 733-410 - www.hofmann-equipment.com

United Kingdom  
Snap-on Equipment Ltd. - Unit 17 Denney Road, King's Lynn - Norfolk PE30 4HG  
Phone: +44 118 929-6811 - Fax: +44 118 966-4369 - www.hofmann-equipment.com